



Mike 12 WiFi Magnetic Mount Whip Antenna

Key Features

- WiFi / WLAN 2.4GHz
- Magnetic Mount
- High Gain



General Description

The Mike 12 is a ½ wave, high gain mag mount whip antenna, tuned to the WiFi/Bluetooth/Zigbee frequencies. With a high peak gain of 5dBi, the Mike 12 is a great antenna for demanding applications.

Its magnetic base provides a versatile method of mounting, allowing the user to move the antenna to optimise signal strength.

Common applications for this antenna are secure compound IoT applications with sensors connected via ZigBee, Home Automation remote controls, WiFi extensions and peer to peer Bluetooth links; especially those in low signal areas.

Alternative connectors and cable lengths can be specified for volume orders.

Additional Considerations

- Flexibility to reposition for best signal
- Suitable for IoT Applications
- Meets all EU compliance criteria for electronic goods



sales

email

web

fax

Registered in England No. 08405712 VAT Registration No. GB163 04 0349 Siretta Ltd Basingstoke Road Spencers Wood Reading Berkshire RG7 1PW +44(0)118 976 9014 +44(0)118 976 9020 sales@siretta.com www.siretta.com






Mike 12 WiFi Magnetic Mount Whip Antenna

Electrical Specifications

Temperature range:	-30 to +70°C
Impedance:	50 ohm
Peak Gain:	5.0dBi
VSWR:	<1.8:1
Frequency range:	2400MHz
Max power:	20W
Polarization:	Omni

Mechanical Specifications

Dimensions:	84mm Ø H: 214.8mm
Weight:	180g
Cable:	RG58
Connector:	SMA Male
Material:	Stainless steel & ABS
Mounting method:	Magnetic



Siretta Ltd Basingstoke Road Spencers Wood Reading Berkshire RG7 1PW

sales +44(0)118 976 9014 +44(0)118 976 9020 email sales@siretta.com web www.siretta.com


fax





Mike 12 WiFi Magnetic Mount Whip Antenna

Return Loss and VSWR



Ordering Details

Part Number

Description

MIKE12/3M/SMAM/RP/S/31

WiFi 2.4~2.5GHz Mag Mount Whip Antenna SMA Male Reverse Polarity

sales

email

web

fax

+44(0)118 976 9014 +44(0)118 976 9020 sales@siretta.com www.siretta.com