



Mike 1B

2G/GPRS & ISM 1/4 Wave Antenna



Key Features

- Magnetic mount
- · Quad band GSM frequencies
- High gain 3.5dBi

General Description

The Mike 1B magnetic mount antenna, a rigid small whip type with a credible 3.5dBi peak gain, is a great performer for its size and used in multiple situations especially where mobility is required.

With a variety of connector options and cable lengths, this unit is ideally suited to metering or alarm panels as well as manufacturers evaluation kits as it provides a fast, reliable fit for installers.

Supplied as standard with a 3m cable and SMA Male connector. Alternative cable lengths and connector types can be specified for volume orders.

Additional Considerations

- Great for temporary installations, evaluation kits
- Allows easy integration on to metal surfaces
- Operates on all 4 worldwide cellular network frequencies
- Meets all EU compliance criteria for electronic goods









Mike 1B

2G/GPRS & ISM 1/4 Wave Antenna

Electrical Specifications

| Operating Temperature: | -45 - +75°C |
|------------------------|-----------------------|
| Storage Temperature: | -45 - +75°C |
| Impedance: | 50 Ohm |
| Gain: | 3.5dBi |
| VSWR: | ≤1.5 |
| Max Input Power: | 60W |
| Operating Frequency: | 850-900, 1800-1900MHz |
| Polarization: | Vertical |

Mechanical Specifications

| Dimensions: | H85mm x 30 Ø base |
|---------------------|-------------------|
| Cable: | RG174 |
| Connector: | SMA Male |
| Mounting Method: | Magnetic |

Ordering Details

Part Number Description

MIKE1B/3M/SMAM/S/S/20 2G/GPRS & ISM 1/4 Wave Antenna